



Moveo® — Acoustic Glass Movable Walls

Flexible and efficient space utilisation is becoming a must for offices, hotels, exhibition centres and studios. Intelligent solutions are often required that facilitate multiple room configurations that combine both the feeling of openness and privacy.

With MOVEO Glass you have at your disposal a movable wall system capable of successfully combining transparency and sound insulated technology. Offered as standard with automated horizontal seals, Moveo is the obvious choice in glazed operable walls solutions.

The clear solution for space utilisation

- ☒ Double glazed TSG with optional blinds.
- ☒ ComforTronic® retractable seals are automatically engaged.
- ☒ Panel thickness 100mm (Acoustic ratings R_w 44 & R_w 50).
- ☒ Minimal frame profile (30mm).
- ☒ No floor track required.



Electrically controlled blinds (Optional)



Minimal frame surround (30mm)

1. Multi-directional suspension system.
2. ComforTronic® seals automatically engage when the panel are positioned in place*.
3. ComforTronic® panel-to-panel control contacts with plug-and-play technology.
4. Convex/Concave vertical profile with a minimal 30mm frame surround.
5. Toughened safety glass (combinations provide Rw44 and Rw50).

** Manual backup operation available in the event of power failure*



VICTORIA / TASMANIA

DORMA Movable Walls Pty. Ltd.
46 Abbott Road,
Hallam VIC 3803
Phone (03) 8795 0233
Fax (03) 8795 0232

AUSTRALIAN CAPITAL TERRITORY

27 Raws Crescent
Hume ACT 2620
Phone (02) 6203 0304
Fax (02) 6260 1810

NEW SOUTH WALES

Unit 10 Block R, 391 Park Road
Regents Park NSW 2143
Phone (02) 9645 8300
Fax (02) 9645 8360

QUEENSLAND

44 Harries Road
Coorparoo, QLD 4151
Phone (07) 3394 6895
Fax (07) 3394 6891

WESTERN AUSTRALIA

185 Claisebrook Road
Perth WA 6000
Phone (08) 9228 8099
Fax (08) 9228 8077

SOUTH AUSTRALIA

2A Meredith Street
Newton SA 5074
Phone (08) 8337 3077
Fax (08) 8336 9431

infomovablewalls@dorma.com
www.dorma.co.nz

NEW ZEALAND

DORMA NZ Ltd.
Building P, 61-69 Patiki Rd
Avondale, Auckland
NEW ZEALAND 1026
Phone +64 (9) 830 2052
Fax +64 (9) 820 4909

sales@dorma.co.nz
www.dorma.co.nz

Dimensions	
Model	Moveo® Glass
Panel Thickness	100mm
Clear height (Min/Max)	2,000mm to 4,000mm
Panel width (Min/Max)	600mm — 1,200mm
Frame profile width	Horizontal 118mm; Vertical 30mm
Glazing	Double-skinned toughened safety glass (TSG)
Construction	
Frame type	Aluminium
Panel-to-panel connection	Large convex/concave aluminium profile with integrated gaskets.
Technology	
Horizontal sealing	ComforTronic® electrically controlled automated sealing
Tracking options	Double point multi-directional tracking
Acoustic Option / Weights	Rw 44 (34Kg/m2)
	Rw 50 (49Kg/m2)
Equipment	
Operating mode	Panels are moved manually, and horizontal sealing activated automatically
Panel types	Standard panel only
Telescopic closure design	Automated telescopic wall jamb (mounted to the fixed wall)